



IPHZ32W Series

Wireless Network Camera

(MPEG-4 / Day & Night)



FEATURES

- Low-latency video streaming with MPEG-4 compression format for sharp and clear images
- **Mobile Surveillance:** Support Symbian s60 v3.0, Mobile Pocket PC operation system
- Supports 802.11 B/G WiFi function
- High performance image sensor with high quality pictures
- Weather-proof, built-in web server with free domain name, can view & recording and update firmware online
- Hybrid digital / analog video output
- Motion detection and alarm notification functions, Image upload over FTP and Email
- External microphone in / audio out for two-way voice communication
- Day & night functionality with Smart Light Control feature for clear and accurate image
- Complete IP surveillance system SuperIPCAM which have 3 languages (English, Spanish, Chinese)

IP FEATURES

1. Use of mature and stable ARM9-MCU+ high-compression chips for hard-coded, compression algorithm was optimized on the basis of MPEG4.
2. The IP module is built-in free domain name, have a Searcher_tool tool to setup and find camera's IP address, and have a 64-CH IP Surveillance system.
3. Support 802.11 B/G WIFI and web surveillance with 20 users simultaneously
4. Support real-time viewing by phone, support Alarm-Mainframe and Cellphone alarm
5. Support the image resolution from QCIF to D1 (720x576) /25FPS.
6. Support 25FPS real-time transmission on WAN, software and web server PTZ control via RS-485 (PELCO-D/PELCO-P protocol)
7. Support image upload over FTP and Email, support PPPoE directly connecting modem and work.
8. Code Rate and Network bandwidth adjustable, frame rate and resolution adjustable, Chinese/English/Spanish menu.
9. Support snapshot and recording online, Support efficient access encryption login purview verification.
10. Can be extended two-way audio
11. Screen characters superimposition, Logo change, rotation image 180 degrees
12. Support for audio and video synchronization. PAN / TILT / ZOOM protocol optional.
13. Security system ensuring long time continuously work and nothing freezes.
14. Hybrid digital / analog video output
15. IP Surveillance system upgrade online, System auto recovery after power reconnected



Shenzhen Xinlianxiang Industry Co.,LTD

SPECIFICATIONS

IPHZ32W series						
◆ Network						
LAN Port	YES					
LAN Speed	10/100 Based-T Ethernet					
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP					
Mobile Surveillance	Support Symbian s60 v3.0, Mobile Pocket PC operation system					
WiFi Features (optional)	(1) Supports 802.11 b/g WiFi (2) Ad-Hoc and infrastructure mode					
Frame Rate	NTSC: 30, PAL: 25					
Number of Online Users	20					
CBR	36Kbps~3Mbps, Image quality and Frame rate adjustable.					
Security	Multiple user access levels with password protection, WEP 64/128 bit					
Web management	The licensed software "SuperIPCAM" for up to 64 network cameras control simultaneously					
◆ Video / Audio						
Video Compression	MPEG4					
Video Remote Control	YES					
Image processing	Support Character, Time, Code rate nestification, Support Privacy Mask					
Video Adjustment	Brightness, Contrast, Saturation and Hue					
Audio Compression	ULaw, 128kbps					
Audio Input	Built-in Microphone, External Microphone Input					
Audio Output	YES					
◆ Camera						
Product name	IPHZ32W-1	IPHZ32W-2	IPHZ32W-3	IPHZ32W-4	IPHZ32BJ22x	IPHZ32BJ30x
Image Sensor	1/4" SONY CCD	1/3" SONY CCD	1/3" SONY HAD CCD		DSP 22x	DSP 30x
TV Line	420TV Line	420TV Line	480TV Line	540TV Line	420TV Line	
Pixels	NTSC: 720(H) x 480(V) / PAL: 720(H) x 576(V)					
Lens	6mm (8, 12,16mm optional) or 22x, 30x Optical Zoom Integrated Camera					
F-number	F1.2					
Viewing Angle	30~60°					
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.					
IR LED	YES					
Min Illumination	0 Lux (20~30m IR ON)					
Video Output	1.0 Vp-p. 75Ω					
BLC	AUTO					
White Balance	ATW					
◆ Others						
Remote Control	YES					
Motion Detection	YES					
Alarm and event Notification	Image upload over FTP and Email					
General I/O	Alarm in x1					
Power	DC 12V, 1A					
Operating Temperature	-10~55℃					
Humidity	10~85%					
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> · Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD · 256 MB RAM · AGP graphics card, Direct Draw, 32MB RAM · Windows Vista, XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later · Internet Explorer 6.x or later 					
Dimension (mm)						
Shipping Weight	excluding mounting bracket and power supply					
In/Out Door Use	Outdoor					

ADDRESS: JianAn garden Compositive Building D602, BaoAn District 9 Area, ShenZhen city, Guangdong Province

TEL: 0755-8375 4030、8375 4050

FAX: 0755-8375 3559

WEBSITE: <http://www.cctv180.com>

EMAIL: dcamera@cctv180.com / sales@cctv180.com / camera180@cctv180.com